

# PSA

WORLD REFINISH PAINTS

# STUCCO VETRO RESINA

## DESCRIZIONE DEL PRODOTTO

**STUCCO VETRO RESINA** Is an unsaturated polyester resin stucco reinforced with fiberglass. Possesses remarkable flexibility, high mechanical, thermal and chemical resistance. Suitable for assembly of fiberglass manufacturates.

## CHARACTERISTICS

- Easy application;
- Allows fast application even at large thickness.

## TECHNICAL SPECIFICATIONS

Product type	Polyester resin.
Colour	Yellow.
Packaging	2 Kg (hardener included)
Specific weight	1400 ± 50g/l.
Storage:	12 months in a fresh and dry room, away from heat sources.

## USEFUL TIPS



Clean thouroughly the support, eliminate oxide residues; degrease with A90 (antisilicone degreaser) Add hardener to stucco according to room temperature:

10 - 20°C	2 - 3 %
More than 20 °C	1 - 2 %

Pot life: 4 - 7 minutes at 20 °C



For spreading once or more times:  
Advised thickness: 200 - 800 micron.



Dry sanding with P40, P80 sandpaper.  
Sanding possible 40 - 45 minutes after application.



Air drying	20 °C
Interval between spreads	8 - 10 minutes.



## SANITARY AND SAFETY REGULATIONS

For professional use.



The information and data contained in this data sheet are based on measurements and the experience acquired in good faith, they are given to the customer who is entitled to verify the application and the definition of eligibility to the use it intends to make. MAXICAR PSA GROUP LTD assumes no responsibility for the results obtained in the specific application made by the user.

MAXICAR - PSA GROUP

VIA L. DA VINCI, 21/23 - TEL. 0935 684005 - 85426 - FAX 0935 686228 - 94015 PIAZZA ARMERINA (EN)  
MAIL info@psa-car.it P.IVA 01087700868

www.psa-car.it