

PSA

WORLD REFINISH PAINTS

REVOLUTION

Universal Metal Stucco

DESCRIPTION

Revolution Universal metal stucco is an unsaturated polyester resin stucco applicable to all metal supports. It presents optimal adhesion to all supports, minimum poring, high spatulability and long resistance to storage.

CHARACTERISTICS

- Easy application;
- Optimal adhesion.

TECHNICAL SPECIFICATIONS

Product type	Polyester resin.
Colour	Grey.
Packaging	2 Kg (hardener included)
Specific weight	1750 g/l.
Storage:	12 months in a fresh and dry room, away from heat sources.

USEFUL TIPS

Clean thoroughly the support, eliminate oxide residues; degrease with **A90** (antisilicone degreaser) Add hardener to stucco according to room temperature:

5 - 10 °C	3 - 3,5 %
10 - 20 °C	2 - 3 %
More than 20 °C	1 - 2 %

Pot life: 4 - 7 minuti a 20 °C.



For spreading once or more times:
Advised thickness: 200 - 900 micron.



Dry sanding with P80, P120, P220 sandpaper.
Sanding possible 30 - 35 after application.



Air drying	20 °C
Interval between spreads	6 - 7 minutes.



SANITARY AND SAFETY REGULATIONS

For professional use.

The information and data contained in this data sheet are based on measurements and the experience acquired in good faith, they are given to the customer who is entitled to verify the application and the definition of eligibility to the use it intends to make. MAXICAR PSA GROUP LTD assumes no responsibility for the results obtained in the specific application made by the user.

MAXICAR - PSA GROUP

VIA L. DA VINCI, 21/23 - TEL. 0935 684005 - 85426 - FAX 0935 686228 - 94015 PIAZZA ARMERINA (EN)

MAIL info@psa-car.it P.IVA 01087700868

www.psa-car.it