

Catalizzatore per trasparente Acrilico 2K HS 2:1

DESCRIPTION

H8 is a HS hardener for universal use. Developed for total compatibility with every two-component paint finish, both acrylic and polyurethane.

CHARACTERISTICS

- -Easy application;
- -Does not yellow.

TECHNICAL SPECIFICATIONS

Product type Aliphatic isocyanate.

Colour Trasparent.
Aspect Lucid.

Packaging 500 MI - 2500 MI. Specific weight $980 \pm 30 \text{ g/l}$.

Storage: Preserve cans well closed in a fresh and dry place; hardeners contain Isocyanates and react to humidity.

USEFUL TIPS



Catalization (in volume):

2 parts T80+1 part H8 HS hardener

Extrafast Touches and painting under 18 °C

Fast Painting between 15 - 20 $^{\circ}$ C Normal Painting between 18 - 28 $^{\circ}$ C

Slow Painting above 28 °C



SANITARY AND SAFETY REGULATIONS

For professional use.

The information and data contained in this data sheet are based on measurements and the experience acquired in good faith, they are given to the customer who is entitled to verify the application and the definition of eligibility to the use it intends to make. MAXICAR PSA GROUP LTD assumes no responsibility for the results obtained in the specific application made by the user.